



Enabler Test Report MMS v1.2

OMA Test Fest (January 2005)

Version 28-Jan-2005

Open Mobile Alliance
OMA-Enabler_Test_Report-MMS-v12-2005-01-28

This document is considered confidential and may not be disclosed in any manner to any non-member of the Open Mobile Alliance™, unless there has been prior explicit Board approval.

This document is a work in process and is not an approved Open Mobile Alliance™ specification. This document is subject to revision or removal without notice. No part of this document may be used to claim conformance or interoperability with the Open Mobile Alliance specifications.

© 2005 Open Mobile Alliance Ltd. All rights reserved.

Terms and conditions of use are available from the Open Mobile Alliance™ Web site at <http://www.openmobilealliance.org/copyright.html>.

You may use this document or any part of the document for internal or educational purposes only, provided you do not modify, edit or take out of context the information in this document in any manner. You may not use this document in any other manner without the prior written permission of the Open Mobile Alliance™. The Open Mobile Alliance authorises you to copy this document, provided that you retain all copyright and other proprietary notices contained in the original materials on any copies of the materials and that you comply strictly with these terms. This copyright permission does not constitute an endorsement of the products or services offered by you.

The Open Mobile Alliance™ assumes no responsibility for errors or omissions in this document. In no event shall the Open Mobile Alliance be liable for any special, indirect or consequential damages or any damages whatsoever arising out of or in connection with the use of this information.

This document is not an Open Mobile Alliance™ specification, is not endorsed by the Open Mobile Alliance and is informative only. This document is subject to revision or removal without notice. No part of this document may be used to claim conformance or interoperability with the Open Mobile Alliance specifications.

Open Mobile Alliance™ members have agreed to use reasonable endeavors to disclose in a timely manner to the Open Mobile Alliance the existence of all intellectual property rights (IPR's) essential to the present document. However, the members do not have an obligation to conduct IPR searches. The information received by the members is publicly available to members and non-members of the Open Mobile Alliance and may be found on the "OMA IPR Declarations" list at <http://www.openmobilealliance.org/ipr.html>. Essential IPR is available for license on the basis set out in the schedule to the Open Mobile Alliance Application Form.

No representations or warranties (whether express or implied) are made by the Open Mobile Alliance™ or any Open Mobile Alliance member or its affiliates regarding any of the IPR's represented on this "OMA IPR Declarations" list, including, but not limited to the accuracy, completeness, validity or relevance of the information or whether or not such rights are essential or non-essential.

This document is available online in PDF format at <http://www.openmobilealliance.org/>.

Known problems associated with this document are published at <http://www.openmobilealliance.org/>.

Comments regarding this document can be submitted to the Open Mobile Alliance™ in the manner published at <http://www.openmobilealliance.org/documents.html>

Contents

1. SCOPE	4
2. REFERENCES.....	5
2.1 NORMATIVE REFERENCES	5
2.2 INFORMATIVE REFERENCES	5
3. TERMINOLOGY AND CONVENTIONS	6
3.1 CONVENTIONS	6
3.2 DEFINITIONS	6
3.3 ABBREVIATIONS	6
4. SUMMARY	7
5. TEST DETAILS.....	8
5.1 DOCUMENTATION.....	8
5.2 TEST CASE STATISTICS	9
5.2.1 Test Case Summary.....	9
5.2.2 Test Case List.....	10
5.2.3 Problem Reports.....	29
6. CONFIRMATION	30
APPENDIX A. CHANGE HISTORY (INFORMATIVE)	31

1. Scope

This report describes the results from the testing carried out at OMA Test Fest (January 2005) concerning MMS enabler version 1.2.

2. References

2.1 Normative References

[OMAIOPPROC]	OMA Interoperability Policy and Process, http://www.openmobilealliance.org/
[MMSEICS]	MMS version 1.2 Enabler Implementation Conformance Statement (EICS), http://www.openmobilealliance.org/
[ERELD]	“Enabler Release Definition for MMS Version 1.2” Open Mobile Alliance™. OMA-ERELD-MMS-v1_2. URL: http://www.openmobilealliance.org/
[MMS_SPEC]	OMA MMS 1.2 specifications
[EPTR]	Enabler Product Test Report
[ETP]	Enabler Test Plan
[ETS]	Enabler Test Specification for MMS 1.2 - OMA-IOP-ETS-MMS-V1_2-20041118-A

2.2 Informative References

3. Terminology and Conventions

3.1 Conventions

This is an informative document, i.e. the document does not intend to contain normative statements.

3.2 Definitions

Client A

The MMS client, which sends a multimedia message (Mobile Originating)

Client B

The MMS client, which receives a multimedia message (Mobile Terminating)

Multimedia Messaging Service (MMS)

A system application by which a client is able to provide a messaging operation with a variety of media types.

MMS Client

The MMS service endpoint located on the client device.

MMS Proxy-Relay

A server, which provides access to various messaging systems.

MMS Server

A server that provides storage and operational support for the MMS service.

MMS SMIL

A SMIL subset defined for MMS purposes.

3.3 Abbreviations

EICS	Enabler Implementation Conformance Statement
EPTR	Enabler Product Test Report
ETP	Enabler Test Plan
ETS	Enabler Test Specification
MM	Multimedia Message
MMS	Multimedia Messaging Service
MMSC	MMS Proxy/Server
OMA	Open Mobile Alliance
PR	Problem Report

4. Summary

This report gives details of the testing carried out during the OMA Test Fest (January 2005) for MMS version 1.2.

The report is compiled on behalf of OMA by NCC Group.

The work and reporting has followed the OMA IOP processes and policies [OMAIOPPROC].

5. Test Details

5.1 Documentation

This chapter lists the details of the enabler and any documentation, tools or test suites used to prove the enabler.

Date:	January 2005
Location:	Madrid, Spain
Enabler:	MMS 1.2
Process:	OMA Interoperability Policy and Process [OMAIOPPROC]
Type of Testing	Interoperability Testing
Products tested:	Client-to-server, Client-to-Client
Test Plan:	MMS Enabler Test Plan [ETP]
Test Specification:	MMS Enabler Test Specification [ETS]
Test Tool:	None
Test Code:	MMS v1.2 Reference Content
Type of Test event:	Test Fest
Participants:	Comverse, Nokia, Openwave Systems Inc. Siemens AG, Sony Ericsson Mobile Communication, tcl&Alcatel <i>2 other participants..</i>
Number of Client Products:	8
Participating Technology Providers for clients:	LG Electronics, Openwave Systems Inc (2 products), Siemens AG, Sony Ericsson Mobile Communication, tcl&Alcatel <i>2 other Client participants.</i>
Number of Server Products:	4
Participating Technology Providers for servers:	Comverse, Nokia, Openwave Systems Inc. <i>1 other Server participant.</i>
Number of test sessions completed:	48 from 50

5.2 Test Case Statistics

5.2.1 Test Case Summary

This chapter gives an overview of the result for all test cases included in [ETS].

The following status is used in the tables below:

- **Total number of TCs:** Used in the summary to indicate how many test cases there are in total.
- **Number of passed:** Used in the summary to indicate how many of the total test cases successfully passed.
- **Number of failed:** Used in the summary to indicate how many of the total test cases failed.
- **Number of N/A:** Used in the summary to indicate how many of the total test cases have not been run due to one of the implementations not supporting the functionality required to run this test case.
- **Number of OT:** Used in the summary to indicate how many of the total test cases have not been run due to no time to run the test case.
- **Number of INC:** Used in the summary to indicate how many of the total test cases have not been run due to functionality not being tested due to an error in the implementation or other functionality that is required to run this test case.

Test Section:	Number of test sessions:	Total number of TCs:	Number of Passed:	Number of Failed:	Number of N/A:	Number of OT:	Number of INC:	Total:
Client to Client TCs	48	44	1106	15	682	263	46	2112
Client to Server TCs	48	56	1566	11	468	617	26	2688
MMSC Transaction TCs	48	9	93	0	114	222	3	432
Client Transaction TCs	48	16	170	23	296	270	9	768
Client B TCs	48	4	84	1	12	88	7	192
E-mail TCs	48	9	227	19	2	184	0	432
Creation Mode TCs	48	6	115	0	4	169	0	288
Content Adaptation	48	12	58	0	81	424	13	576
Total	48	156	3419	69	1659	2237	104	7488

5.2.2 Test Case List

This chapter lists the statistics for all test cases included in [ETS].

The following status is used in the tables below:

- **No. of runs(R):** Used to indicate how many times the test cases have been run in total.
- **No. of passed(P):** Used to indicate how many times the test case has been run with successful result.
- **No. of failed(F):** Used to indicate how many times the test case has been run with failed result
- **No. of OT(O):** Used to indicate how many times the test case has not been run due to no time available.
- **No. of INC(I):** Used to indicate how many times the test case has not been run due to errors being found in other functionality required for running this test case.
- **PR:** Used to indicate if any PRs (Problem Reports) have been issued during testing.
- **Note:** Used to indicate the cause of Inconclusive or Fail verdicts.

Test Case:	Test Case Description:	R	P	F	O	I	PR:	Note:
MMS-1.2-int-101	Removed	0	0	0	0	0		Test Case De-Selected
MMS-1.2-int-102	The purpose is to verify that messages with SMIL layouts, here portrait with text above the image, is correctly sent from Client A to Client B and that the received message is reasonably presented.	44	32	5	6	1		
MMS-1.2-int-103	The purpose is to verify that messages with SMIL layouts, here portrait with text below the image, is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	41	0	6	1		
MMS-1.2-int-104	The purpose is to verify that messages with SMIL layouts, here landscape with text to the left of the image, is correctly sent from Client A to Client B and that the received message is reasonably presented.	18	14	0	3	1		
MMS-1.2-int-105	The purpose is to verify that messages with SMIL layouts, here landscape with text to the right of the image, is correctly sent from Client A to Client B and that the received message is reasonably presented.	18	14	0	3	1		

MMS-1.2-int-106	The purpose is to verify that multiple objects (one image, one text and one audio file) are correctly sent from Client A to Client B and that all contents of the received message is reasonably presented.	48	40	0	7	1		
MMS-1.2-int-107	The purpose is to verify that multiple pages are correctly sent from Client A to Client B and that all pages are reasonably presented in the correct order.	47	40	0	6	1		
MMS-1.2-int-108	The purpose is to verify that multiple pages and objects with page timing are correctly sent from Client A to Client B and that all pages and objects are reasonably presented in the correct order. The timing of the pages follows the specified values or client default values.	48	40	0	7	1		
MMS-1.2-int-109	The purpose is to verify that messages with different SMIL page timing can be sent, received and reasonably presented. This message contains 4 different pages and page times: - Page 1 with page timing 100 ms or client minimum - Page 2 with 5 seconds page timing - Page 3 with page time 20 seconds or client maximum - Page 4 with no page timing Note: Since the last page of a SMIL presentation can be shown indefinitely on a client until further actions, this fourth page is only used for delimitating the period of time that page 3 is displayed. It is then possible to verify that the timing of page 3 received by Client B is the same that was set by Client A.	48	40	0	7	1		
MMS-1.2-int-110	Removed	0	0	0	0	0		Test Case De-Selected
MMS-1.2-int-111	The purpose is to verify that a subject field encoded in UTF-8 correctly sent from Client A to Client B and that the message subject is textually correct.	48	38	1	7	2		
MMS-1.2-int-112	The purpose is to verify that a text object with US-ASCII encoding is correctly sent from Client A to Client B and that the received message is textually correct.	42	35	0	6	1		

MMS-1.2-int-113	The purpose is to verify that a text object with UTF-8 encoding is correctly sent from Client A to Client B and that the received message is textually correct.	48	40	0	7	1		
MMS-1.2-int-114	Removed	0	0	0	0	0		Test Case De-Selected
MMS-1.2-int-115	The purpose is to verify that a JPG image of the size 80x60 is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	40	0	7	1		
MMS-1.2-int-116	The purpose is to verify that a JPG image of the size 160x120 is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	40	0	7	1		
MMS-1.2-int-117	The purpose is to verify that a JPG image of the size 60x80 is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	40	0	7	1		
MMS-1.2-int-118	The purpose is to verify that a JPG image of the size 640x480 is correctly sent from Client A to Client B and that the received message is reasonably presented.	46	36	0	9	1		
MMS-1.2-int-119	The purpose is to verify that a GIF87a image of the size 80x60 is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	39	0	8	1		
MMS-1.2-int-120	The purpose is to verify that a GIF87a image of the size 160x120 is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	39	0	8	1		
MMS-1.2-int-121	The purpose is to verify that a GIF87a image of the size 60x80 is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	39	0	8	1		
MMS-1.2-int-122	The purpose is to verify that a GIF87a image of the size 640x480 is correctly sent from Client A to Client B and that the received message is reasonably presented.	31	25	0	4	2		

MMS-1.2-int-123	The purpose is to verify that an animated GIF89a image of the size 80x60 is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	38	0	9	1		
MMS-1.2-int-124	The purpose is to verify that an animated GIF89a image of the size 160x120 is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	38	0	9	1		
MMS-1.2-int-125	The purpose is to verify that an animated GIF89a image of the size 60x80 is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	38	0	9	1		
MMS-1.2-int-126	The purpose is to verify that an animated GIF89a image of the size 640x480 is correctly sent from Client A to Client B and that the received message is reasonably presented.	31	24	0	5	2		
MMS-1.2-int-127	The purpose is to verify that a WBMP image of the size 80x60 is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	39	0	8	1		
MMS-1.2-int-128	The purpose is to verify that a WBMP images of the size 160x120 is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	39	0	8	1		
MMS-1.2-int-129	The purpose is to verify that a WBMP images of the size 60x80 is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	39	0	8	1		
MMS-1.2-int-130	The purpose is to verify that a WBMP images of the size 640x480 is correctly sent from Client A to Client B and that the received message is reasonably presented.	31	24	0	5	2		
MMS-1.2-int-131	The purpose is to verify that an AMR audio NB object/content is correctly sent from Client A to Client B and that the AMR audio NB file/object is reasonably presented.	48	36	0	11	1		

MMS-1.2-int-132	The purpose is to verify that an 13k speech object/content is correctly sent from Client A to Client B and that the 13k speech file/object is reasonably presented.	7	1	0	4	2		
MMS-1.2-int-133	The purpose is to verify that a QCIF video file/object is correctly sent from Client A to Client B and that the QCIF video file/object is reasonably presented.	43	31	0	11	1		
MMS-1.2-int-134	The purpose is to verify that a sub-QCIF video file/object is correctly sent from Client A to Client B and that the sub-QCIF video file/object is reasonably presented.	41	32	0	8	1		
MMS-1.2-int-135	The purpose is to verify that a QCIF video file/object is correctly sent from Client A to Client B and that the QCIF video file/object is reasonably presented.	6	2	0	3	1		
MMS-1.2-int-136	The purpose is to verify that a QCIF video file/object is correctly sent from Client A to Client B and that the QCIF video file/object is reasonably presented.	5	1	0	3	1		
MMS-1.2-int-137	The purpose is to verify that a QCIF video file/object is correctly sent from Client A to Client B and that the QCIF video file/object is reasonably presented.	4	0	0	3	1		
MMS-1.2-int-138	The purpose is to verify that a QCIF video file/object is correctly sent from Client A to Client B and that the QCIF video file/object is reasonably presented.	5	1	0	3	1		
MMS-1.2-int-139	The purpose is to verify that a sub-QCIF video file/object is correctly sent from Client A to Client B and that the sub-QCIF video file/object is reasonably presented.	4	0	0	3	1		
MMS-1.2-int-140	The purpose is to verify that a sub-QCIF video file/object is correctly sent from Client A to Client B and that the sub-QCIF video file/object is reasonably presented.	5	1	0	3	1		

MMS-1.2-int-141	The purpose is to verify that a sub-QCIF video file/object is correctly sent from Client A to Client B and that the sub-QCIF video file/object is reasonably presented.	4	0	0	3	1		
MMS-1.2-int-142	The purpose is to verify that a sub-QCIF video file/object is correctly sent from Client A to Client B and that the sub-QCIF video file/object is reasonably presented.	5	1	0	3	1		
MMS-1.2-int-143	The purpose is to verify that a vCard object correctly sent from Client A to Client B and that the received vCard is textually correct.	41	26	4	10	1		
MMS-1.2-int-144	The purpose is to verify that a vCalendar object correctly sent from Client A to Client B and that the received vCalendar is textually correct.	40	23	5	11	1		
MMS-1.2-int-201	Removed	0	0	0	0	0		Test Case De-Selected
MMS-1.2-int-202	The purpose is to verify that a message in Image Basic Content Class with size under 30k can be sent from Client A to Client B and that the received message is reasonably presented.	48	34	0	14	0		
MMS-1.2-int-203	The purpose is to verify that a message in Image Rich Content Class with size under 100k can be sent from Client A to Client B and that the received message is reasonably presented.	48	33	0	15	0		
MMS-1.2-int-204	The purpose is to verify that a message in Video Rich Content Class with size under 300k can be sent from Client A to Client B and that the received message is reasonably presented.	46	23	6	17	0		
MMS-1.2-int-205	The purpose is to verify that multiple pages and objects with page timing are correctly sent from Client A to Client B via the MMSC and that all pages and objects are reasonably presented in the correct order. The timing of the pages follows the specified values or client default values.	48	37	0	11	0		
MMS-1.2-int-206	The purpose is to verify that a message with UTF-8 characters in the Subject-field is correctly sent from Client A to Client B via MMSC and that the message is successfully received and the subject is textually correct.	48	36	0	12	0		

MMS-1.2-int-207	The purpose is to verify that a message with 40 chars in the Subject-field is correctly sent from Client A to Client B via MMSC and that the message is successfully received and the subject is textually correct.	48	34	0	14	0		
MMS-1.2-int-208	The purpose is to verify that a messages with US-ASCII characters in the Subject-field is correctly sent from Client A to Client B via MMSC and that the message is successfully received and the subject is textually correct.	37	28	0	9	0		
MMS-1.2-int-209	The purpose is to verify that a message with US-ASCII characters in the To-field is correctly sent from Client A to Client B via MMSC and that the message is successfully received.	37	29	0	8	0		
MMS-1.2-int-210	The purpose is to verify that a message with US-ASCII characters in the Cc-field is correctly sent from Client A to Client B via MMSC and that the message is successfully received.	37	29	0	8	0		
MMS-1.2-int-211	The purpose is to verify that a message with US-ASCII characters in the Bcc-field is correctly sent from Client A to Client B via MMSC and that the message is successfully received.	30	22	0	8	0		
MMS-1.2-int-212	The purpose is to verify that a message with UTF-8 characters in the To-field is correctly sent from Client A to Client B via MMSC and that the message is successfully received.	37	26	0	10	1		
MMS-1.2-int-213	The purpose is to verify that a message with UTF-8 characters in the CC-field is correctly sent from Client A to Client B via MMSC and that the message is successfully received.	38	23	0	14	1		
MMS-1.2-int-214	The purpose is to verify that a message with UTF-8 characters in the BCC-field is correctly sent from Client A to Client B via MMSC and that the message is successfully received.	36	21	0	14	1		
MMS-1.2-int-215	The purpose is to verify that a message is correctly sent from Client A to Client B via MMSC and that the message is successfully received and message priority is set to Normal.	48	38	0	10	0		

MMS-1.2-int-216	The purpose is to verify that a message is correctly sent from Client A to Client B via MMSC and that the message is successfully received and message priority is set to Low.	48	35	0	13	0		
MMS-1.2-int-217	The purpose is to verify that a message is correctly sent from Client A to Client B via MMSC and that the message is successfully received and message priority is set to High.	48	36	0	12	0		
MMS-1.2-int-218	The purpose is to verify that a message with Message Class Personal is correctly sent from Client A to Client B via MMSC and that the message is successfully received with a Message Class of Personal.	32	23	0	9	0		
MMS-1.2-int-219	The purpose is to verify that a text object with US-ASCII encoding is correctly sent from Client A to Client B via the MMSC and that the received message is textually correct.	33	23	0	10	0		
MMS-1.2-int-220	The purpose is to verify that a text object with UTF-8 encoding is correctly sent from Client A to Client B via the MMSC and that the received message is textually correct.	48	35	0	13	0		
MMS-1.2-int-221	Removed	0	0	0	0	0		Test Case De-Selected
MMS-1.2-int-222	The purpose is to verify that a JPG image of the size 80x60 is correctly sent from Client A to Client B via the MMSC and that the received message is reasonably presented.	48	39	0	9	0		
MMS-1.2-int-223	The purpose is to verify that a JPG image of the size 160x120 is correctly sent from Client A to Client B via the MMSC and that the received message is reasonably presented.	48	39	0	9	0		
MMS-1.2-int-224	The purpose is to verify that a JPG image of the size 60x80 is correctly sent from Client A to Client B via the MMSC and that the received message is reasonably presented.	48	39	0	9	0		
MMS-1.2-int-225	The purpose is to verify that a JPG image of the size 640x480 is correctly sent from Client A to Client B and that the received message is reasonably presented.	48	36	0	12	0		

MMS-1.2-int-226	The purpose is to verify that a GIF87a image of the size 80x60 is correctly sent from Client A to Client B via the MMSC and that the received message is reasonably presented.	48	38	0	10	0		
MMS-1.2-int-227	The purpose is to verify that a GIF87a image of the size 160x120 is correctly sent from Client A to Client B via the MMSC and that the received message is reasonably presented.	48	38	0	10	0		
MMS-1.2-int-228	The purpose is to verify that a GIF87a image of the size 60x80 is correctly sent from Client A to Client B via the MMSC and that the received message is reasonably presented.	48	38	0	10	0		
MMS-1.2-int-229	The purpose is to verify that a GIF87a image of the size 640x480 is correctly sent from Client A to Client B and that the received message is reasonably presented.	36	28	0	7	1		
MMS-1.2-int-230	The purpose is to verify that an animated GIF89a image of the size 80x60 is correctly sent from Client A to Client B via the MMSC and that the received message is reasonably presented.	48	37	0	10	1		
MMS-1.2-int-231	The purpose is to verify that an animated GIF89a image of the size 160x120 is correctly sent from Client A to Client B via the MMSC and that the received message is reasonably presented.	48	37	0	10	1		
MMS-1.2-int-232	The purpose is to verify that an animated GIF89a image of the size 60x80 is correctly sent from Client A to Client B via the MMSC and that the received message is reasonably presented.	48	37	0	10	1		
MMS-1.2-int-233	The purpose is to verify that an animated GIF89a image of the size 640x480 is correctly sent from Client A to Client B and that the received message is reasonably presented.	36	27	0	7	2		
MMS-1.2-int-234	The purpose is to verify that a WBMP image of the size 80x60 is correctly sent from Client A to Client B via the MMSC and that the received message is reasonably presented.	48	37	0	10	1		

MMS-1.2-int-235	The purpose is to verify that a WBMP images of the size 160x120 is correctly sent from Client A to Client B via the MMSC and that the received message is reasonably presented.	48	36	0	11	1		
MMS-1.2-int-236	The purpose is to verify that a WBMP images of the size 60x80 is correctly sent from Client A to Client B via the MMSC and that the received message is reasonably presented.	48	36	0	11	1		
MMS-1.2-int-237	The purpose is to verify that a WBMP images of the size 640x480 is correctly sent from Client A to Client B and that the received message is reasonably presented.	36	25	0	9	2		
MMS-1.2-int-238	The purpose is to verify that an AMR audio NB object/content is correctly sent from Client A to Client B via the MMSC and that the AMR audio NB file/object is reasonably presented.	48	33	0	14	1		
MMS-1.2-int-239	The purpose is to verify that an 13k speech object/content is correctly sent from Client A to Client B and that the 13k speech file/object is reasonably presented.	15	6	0	8	1		
MMS-1.2-int-240	The purpose is to verify that a QCIF video file/object is correctly sent from Client A to Client B and that the QCIF video file/object is reasonably presented.	45	31	0	14	0		
MMS-1.2-int-241	The purpose is to verify that a sub-QCIF video file/object is correctly sent from Client A to Client B and that the sub-QCIF video file/object is reasonably presented.	45	32	0	13	0		
MMS-1.2-int-242	The purpose is to verify that a sub-QCIF video file/object is correctly sent from Client A to Client B and that the sub-QCIF video file/object is reasonably presented.	14	4	0	9	1		
MMS-1.2-int-243	The purpose is to verify that a sub-QCIF video file/object is correctly sent from Client A to Client B and that the sub-QCIF video file/object is reasonably presented.	14	4	0	9	1		

MMS-1.2-int-244	The purpose is to verify that a sub-QCIF video file/object is correctly sent from Client A to Client B and that the sub-QCIF video file/object is reasonably presented.	14	4	0	9	1		
MMS-1.2-int-245	The purpose is to verify that a sub-QCIF video file/object is correctly sent from Client A to Client B and that the sub-QCIF video file/object is reasonably presented.	14	4	0	9	1		
MMS-1.2-int-246	The purpose is to verify that a vCard object is correctly sent from Client A to Client B via the MMSC and that the received vCard is textually correct.	45	30	1	14	0		
MMS-1.2-int-247	The purpose is to verify that a vCalendar object correctly sent from Client A to Client B via the MMSC and that the received vCalendar is textually correct.	43	29	1	13	0		
MMS-1.2-int-248	The purpose is to verify that a message with an MSISDN/MDN address in the "To:"-field is correctly sent from Client A to Client B via MMSC server and that the message is successfully received.	47	35	0	12	0		
MMS-1.2-int-249	The purpose is to verify that a message with an MSISDN/MDN address in the "Cc:"-field is correctly sent from Client A to Client B via MMSC server and that the message is successfully received.	47	34	0	12	1		
MMS-1.2-int-250	The purpose is to verify that a message with MSISDN/MDN address in the "Bcc:"-field is correctly sent from Client A to Client B via MMSC server and that the message is successfully received.	37	24	0	12	1		
MMS-1.2-int-251	The purpose is to verify that messages can be simultaneously and correctly sent from Client A to multiple MSISDN/MDN clients and multiple email recipients via MMSC and that the message is successfully received by all the recipients listed in the "To:"-field.	47	31	1	15	0		

MMS-1.2-int-252	The purpose is to verify that messages can be simultaneously and correctly sent from Client A to multiple MSISDN/MDN clients and multiple email recipients via MMSC and that the message is successfully received by all the recipients listed in the "Cc:"-field.	47	29	1	16	1		
MMS-1.2-int-253	The purpose is to verify that messages can be simultaneously and correctly sent from Client A to multiple MSISDN/MDN clients and multiple email recipients via MMSC and that the message is successfully received by all the recipients listed in the "Bcc:"-field.	37	19	1	16	1		
MMS-1.2-int-254	The purpose is to verify that a message with a single email address in the "To:"-field is correctly sent from Client A to Client B via MMSC server and that the message is successfully received.	48	33	0	15	0		
MMS-1.2-int-255	The purpose is to verify that a message with a single email address in the "Cc:"-field is correctly sent from Client A to Client B via MMSC server and that the message is successfully received.	48	31	0	16	1		
MMS-1.2-int-256	The purpose is to verify that a message with a single email address in the Bcc-field is correctly sent from Client A to Client B via MMSC server and that the message is successfully received.	38	21	0	16	1		
MMS-1.2-int-301	The purpose is to verify that a message with the From-field left empty is correctly sent from Client A to Client B via MMSC and that the MMSC has processed/validated and inserted the correct MSISDN/MDN number of Client A and the message is successfully received with the correct MSISDN/MDN number of Client A in the From-field of the message.	27	17	0	10	0		
MMS-1.2-int-302	The purpose is to verify that a message sent with a Validity Period/Expiry Time, set by the client, is accepted by the MMSC.	47	28	0	19	0		

MMS-1.2-int-303	The purpose is to verify that a message Validity Period/Expiry Time set by the client can be overwritten or redefined by the MMSC.	43	16	0	27	0		
MMS-1.2-int-304	The purpose is to verify that a message sent with a Delivery Time, set by the Client A, is delivered at the specified time to the receiving Client B.	26	13	0	12	1		
MMS-1.2-int-305	The purpose is to verify that when a client does not set the message time stamp, the MMSC will set the time stamp.	24	4	0	18	2		
MMS-1.2-int-306	The purpose is to verify that the MMSC sets the X-Mms-Retrieve-Status field to Error-permanent-service-denied = <Octet 225 > when the corresponding retrieval attempt was rejected due to failure of authentication or authorization of the originating MMS Client and that the client acts in a proper way according to the Retrieve Status code.	33	0	0	33	0		
MMS-1.2-int-307	The purpose is to verify that the MMSC sets the X-Mms-Retrieve-Status field to Error-permanent-message-not-found = <Octet 225 > when the content location URL in the retrieval attempt does not point to an MM and that the client acts in a proper way according to the Retrieve Status code.	43	8	0	35	0		
MMS-1.2-int-308	The purpose is to verify that the MMSC sets the X-Mms-Retrieve-Text field to the Retrieve text value and that Client B displays the Retrieve text when the corresponding retrieval attempt was rejected due to failure of authentication or authorization of the originating MMS Client.	33	0	0	33	0		
MMS-1.2-int-309	The purpose is to verify that the MMSC sets the X-Mms-Retrieve-Text field to the Retrieve text value and that Client B displays the Retrieve text when the content location URL in the retrieval attempt does not point to an MM.	42	7	0	35	0		

MMS-1.2-int-401	The purpose is to verify that a message with a request for delivery report is correctly sent from Client A to Client B via MMSC and that the originator can receive a delivery report with the Retrieved status after successful message delivery.	47	20	6	21	0		
MMS-1.2-int-402	The purpose is to verify that a message with a request for delivery report from Client A to Client B via MMSC and that the originator can receive a delivery report with the Rejected status after message rejection.	41	16	6	19	0		
MMS-1.2-int-403	The purpose is to verify that a message with a request for delivery report from Client A to Client B and that the originator can receive a delivery report with the Expired status after message expiration.	48	21	6	21	0		
MMS-1.2-int-404	The purpose is to verify that a message with a request for delivery report from Client A to multiple recipients and that the originator can receive a separate delivery report for each recipient, with the correct Delivery Status for each recipient after message delivery or message delivery attempt (in the case of Expired Status) to each separate recipient.	43	15	2	26	0		
MMS-1.2-int-405	The purpose is to verify that a message with a request for Read-Reply report is correctly sent from Client A to Client B via MMSC and that the read report contains the date on which the message was read	35	21	0	14	0		
MMS-1.2-int-406	The purpose is to verify that a message with a request for Read-Reply report is correctly sent from Client A to Client B via MMSC and that the originator can receive a read report after message has been read and that the current date of the read report is set by the MMSC when not set by Client B.	29	10	1	15	3		
MMS-1.2-int-407	The purpose is to verify that a message with a request for a Read-Reply report is correctly sent from Client A to multiple recipients via MMSC and that the originator can receive a separate and correct Read-Reply report from each recipient after the message has been read by each recipient.	35	15	2	18	0		

MMS-1.2-int-408	The purpose is to verify that a message with a request for Read-Reply report is correctly sent from Client A to Client B via MMSC and that the originator can receive a read report after message has been read	35	19	0	16	0		
MMS-1.2-int-409	The purpose is to verify that a message that is forwarded without prior retrieval has the previously sent-by field set to the originator of the initial message.	20	3	0	14	3		
MMS-1.2-int-410	The purpose is to verify that a message that is forwarded without prior retrieval has the previously sent-date field set to the date of the initial message.	20	3	0	14	3		
MMS-1.2-int-411	The purpose is to verify that a message addressed to a client can be forwarded without prior retrieval. The originally addressed client shall NOT retrieve the message. The messages forwarded from one client to another client shall be received in full and be reasonably presented.	19	6	0	13	0		
MMS-1.2-int-412	The purpose is to verify that a message forwarded with a Validity Period/Expiry Time, set by the client, is accepted by the MMSC.	23	5	0	18	0		
MMS-1.2-int-413	The purpose is to verify that a messages addressed to a client can be forwarded without prior retrieval. The originally addressed client shall NOT retrieve the message. The messages forwarded from one client to another client shall be received in full and be reasonably presented. The forwarding Client B can receive a delivery report with the Retrieved status after successful message delivery.	19	4	0	15	0		
MMS-1.2-int-414	The purpose is to verify that a messages addressed to a client can be forwarded without prior retrieval. The originally addressed client shall NOT retrieve the message. The forwarding Client B can receive a delivery report with the Rejected status after message rejection.	19	4	0	15	0		

MMS-1.2-int-415	The purpose is to verify that a message addressed to a client can be forwarded without prior retrieval. The originally addressed client shall NOT retrieve the message. The forwarding Client B can receive a delivery report with the Expired status after message expiration.	19	4	0	15	0		
MMS-1.2-int-416	The purpose is to verify that a message addressed to a client can be forwarded without prior retrieval. The originally addressed client shall NOT retrieve the message. The forwarding Client B can receive a read report after message has been read.	20	4	0	16	0		
MMS-1.2-int-501	The purpose is to verify that a message is correctly sent from Client A to Client B and that the message is immediately retrieved by using the Immediate Retrieval mode.	48	30	0	18	0		
MMS-1.2-int-502	The purpose is to verify that a message is correctly sent from Client A to Client B and that the message is retrieved by using the Deferred Retrieval mode.	48	26	0	22	0		
MMS-1.2-int-503	The purpose is to verify that a message is correctly sent from Client A to Client B and that Client B can reject the messages and not attempt message download.	39	19	0	20	0		
MMS-1.2-int-504	The purpose is to verify that the terminal is able to receive a message containing DRM protected content and that the received objects are properly protected.	45	9	1	28	7		
MMS-1.2-int-601	The purpose is to verify that a text object is correctly sent from Client A to an email recipient via MMSC and that the received message is reasonably presented.	48	29	0	19	0		
MMS-1.2-int-602	The purpose is to verify that an image object is correctly sent from Client A to an email recipient via MMSC and that the received message is reasonably presented.	48	29	0	19	0		
MMS-1.2-int-603	The purpose is to verify that an audio object is correctly sent from Client A to an email recipient via MMSC and that the received message is reasonably presented.	48	27	1	20	0		

MMS-1.2-int-604	The purpose is to verify that that a message with multiple objects (text, image, audio and presentation) is correctly sent from Client A to an email recipient via MMSC and that the received message is reasonably presented.	48	28	1	19	0		
MMS-1.2-int-605	The purpose is to verify that a message with multiple objects (text, image, audio and presentation) is correctly sent from an email sender to an MMS client (Client B) via MMSC and that the received message is reasonably presented.	48	22	7	19	0		
MMS-1.2-int-606	The purpose is to verify that a vCard object is correctly sent from Client A to an email recipient via MMSC and that the received vCard is textually correct.	48	25	1	22	0		
MMS-1.2-int-607	The purpose is to verify that a vCalendar object correctly sent from Client A to an email recipient via MMSC and that the received vCalendar is textually correct.	48	24	2	22	0		
MMS-1.2-int-608	The purpose is to verify that a vCard object correctly sent from an email sender to an MMS client (ClientB) via MMSC and that the received vCard is textually correct.	48	21	5	22	0		
MMS-1.2-int-609	The purpose is to verify that a vCalendar object is correctly sent from Client A to an email recipient via MMSC and that the received vCalendar is textually correct.	46	22	2	22	0		
MMS-1.2-int-701	The purpose is to verify that oversized content added to a message is refused in RESTRICTED mode in Client A and that the device is limited to the addition of allowable content within the core domain.	44	23	0	21	0		
MMS-1.2-int-702	The purpose is to verify that content outside core domain is prohibited when Client A is in RESTRICTED mode.	48	27	0	21	0		
MMS-1.2-int-703	The purpose is to verify that inclusion content with oversized image resolution not belonging to the core domain is prohibited when Client A is in RESTRICTED mode.	48	22	0	26	0		

MMS-1.2-int-704	The purpose is to verify that a non conformant message is refused to be forwarded when Client A is in RESTRICTED mode.	48	15	0	33	0		
MMS-1.2-int-705	The purpose is to verify that a non conformant message is refused to be forwarded when Client A is in RESTRICTED mode.	48	16	0	32	0		
MMS-1.2-int-706	The purpose is to verify that a message containing non conformant content is refused to be forwarded when Client A is in RESTRICTED mode.	48	12	0	36	0		
MMS-1.2-con-801	The purpose is to verify that the MMS Relay/Server has mechanisms to enable or disable major content adaptation.	44	6	0	38	0		
MMS-1.2-con-802	The purpose is to verify that the MMS Relay/Server has a mechanism to make available the original content of the MM to the end-user when major content adaptation is or needs to be applied	37	0	0	32	5		
MMS-1.2-con-803	The purpose is to verify that the MMS Relay/Server updates labels in the presentation element after media type adaptation is applied	42	5	0	37	0		
MMS-1.2-con-804	The purpose is to verify that the MMS Relay/Server updates the file extensions and MIME types after media format adaptation is applied.	44	6	0	38	0		
MMS-1.2-con-805	The purpose is to verify that an image with a greater resolution than 160x120 is correctly sent from Client A larger than Image Basic Content Class to Client B in Content Class Image Basic and that the received image is less than or equal to 160x120.	43	7	0	36	0		
MMS-1.2-con-806	The purpose is to verify that a GIF87 image larger than 30k is correctly sent from Client A larger than Image Basic Content Class to Client B in Content Class Image Basic and that the received image is less than or equal to 30k.	33	6	0	27	0		

MMS-1.2-con-807	The purpose is to verify that a JPEG image larger than 30k is correctly sent from Client A larger than Image Basic Content Class to Client B in Content Class Image Basic and that the received image is less than or equal to 30k.	43	7	0	36	0		
MMS-1.2-con-808	The purpose is to verify that a GIF89 image larger than 30k is correctly sent from Client A larger than Image Basic Content Class to Client B in Content Class Image Basic and that the received image is less than or equal to 30k in GIF87 (or JPEG).	34	6	0	28	0		
MMS-1.2-con-809	The purpose is to verify that a SP-MIDI file larger than 30k is correctly sent from Client A larger than Image Basic Content Class to Client B in Content Class Image Basic and that the received message does not contain the file.	44	6	0	38	0		
MMS-1.2-con-810	The purpose is to verify that a video file is correctly sent from Client A (either in content class Video Basic or Video rich) to Client B in Content Class Image Basic and that the received image is less than or equal to 30k and has a resolution of 160x120 or less.	44	7	0	37	0		
MMS-1.2-con-811	The purpose is to verify that a video file is correctly sent from Client A (either in content class Video Basic or Video Rich) to Client B in Content Class Image Rich and that the received image is less than or equal to 100k.	44	1	0	39	4		
MMS-1.2-con-812	The purpose is to verify that a video file larger than 100k is correctly sent from Client A in content class Video Rich to Client B in Content Class Video Basic and that the received video file is less than or equal to 100k.	43	1	0	38	4		

5.2.3 Problem Reports


During the activities for TestFest-8, the following problem reports were generated relating to the test materials and test process:

PR Number	Affecting	Description	Test Case reference / Specification reference
0001	Pre-Testing	Inconclusive Test Results for Pre-Test testcase.	CON-812
0002	ETS Test Session Report	Client to Server Test should have their own separate report	601-609, 701-706, 801-802.
0003	ETS	Can the value of the filename = parameter in an attachment be Ascii Encoded	-
0004	Test Content	Content in Test Object "John.Doe.vcf" should not contain UTF-8 encoding	MMS-1.2-int-606
0005	EICS	Inconsistencies in OMA-ICS-MMS-Client-V1_2_0-20040406-A - references to non-existent SCR items	Client EICS
0006	EICS	Inconsistency in Client EICs relating to references to SCR item MMSCONF- MED-C-022	Client EICS
0007	EICS	Clarification on the applicability of the "Support in send" column for MMSCONF-IBC-C-007 in Client EICS	Client EICS
0008	EICS	Inconsistency for mandatory SCR item MMSCONF-CAG-S-006 in Server EICS	Server EICS
0009	ETS	There are too many duplicate test cases, and too many test cases in general.	All
0010	ETS	Confusion over "Client-Server" and "Client-Client" test cases	All

Full details of the Problem Reports can be found at: <http://www.opengroup.org:8000/OMA-PR/>

6. Confirmation

This signature states that the included information is true and valid.

A handwritten signature in blue ink, appearing to read "Stephen Higgins", with a stylized flourish at the end.

Stephen Higgins - MMS Trusted Zone

Appendix A. Change History (Informative)

Type of Change	Date	Section	Description